



Tension Form Finisher

Model 607TFF



- Adjustable shoulder expanders
- Operates with full tensioning when required
- Form raises additional 30 inches for longer garments
- Operates without tensioning for non-stretchable garments
- Finishes men's and ladies' coats, jackets, dresses, shirts, blouses
- Front and rear clamps for tensioning and non-tensioning garments
- Semi-automatic vent clamps close manually, auto release at end of cycle

www.forentausa.com

Tel: 423-586-5370 • Email: info@forentausa.com

Made in USA

Specifications

Model 607TF

Electrical connections		
208-230V 3PH 50/60Hz 8 amps 3.2kW		standard
380-415V 3PH 50/60Hz 4 Amps 3.2 kW with 220 volt neutral		optional
Steam, air and water connections		
Steam inlet	NPT	1/2"
Steam outlet	NPT	1/2"
Recommended steam pressure	psig kPa	75-85 517-586
Steam consumption @ 85 psig	lb/hr	69
Steam consumption @ 586 kPa	kg/hr	31
	BHP	2
Compressed air connection	NPT	3/8"
Recommended compressed air pressure	psig kPa	65 448
Compressed air consumption		
free air/cycle @ 65 psig		0.11 ft ³
free air/cycle @ 586 kPa		3.1 liter
Water connection (for water spray)	NPT	1/4"
Weight (crated)		
	lbs kg	400 182
Shipping		
1 Steam connection	4 Air connection	
2 Steam outlet	5 Electrical connection	
3 Control panel	6 Water connection (for optional water spray)	

