



Spotting Boards

Models 44SP/44SPG



Model 44SP

- Heated air for faster drying
- Integrated vacuum available
- Unique design assures no steam leaks
- Available with stainless steel or glass top
- Fabric catch rack swivels to hold garments while spotting
- Foot pedals allow operator to control flow of steam, air and vacuum

www.forentausa.com

Tel: 423-586-5370 • Email: info@forentausa.com

Made in USA

Specifications

Models 44SP / 44SPG

Steam and Air connection			44SP/44SPG
Steam Inlet	NPT		1/2"
Steam Outlet	NPT		1/2"
Recommended steam pressure	PSIG		75-85
	kPa		517-586
Steam consumption @ 80psig(552 kPa)	BHP		1
	kg/hr		15.6
	lb/hr		34.5
Compressed air	NPT		1/2"
Air consumption	free air/cycle at 80psig		3.0 cu.ft.
	free air/cycle at 552kPa		85 liters
Recommended air pressure	PSIG		80
	kPa		552
Air Vacuum Connection	NPT		1 1/4"
Optional Vacuum Motor Attachment Electrical			
Voltage: 110-120VAC, 1PH, 60Hz, 8.1 Amps (Cord Connected)			
Voltage: 220VAC, 1PH, 60Hz, 4.1 Amps (Cord Connected)			
Weight (crated)			
Shipping	lbs		244
	kg		111
1 Steam Connection 3 Air Connection 5 Optional Vacuum motor 2 Steam Outlet 4 Air Vacuum Connection 6 Vacuum On/Off Switch			

Detail Line Drawing

(millimeters shown in parentheses)

